

ITEM	BRAND	DESCRIPTION	QUANTITY	PRICE EACH	Company
INSTALLATION					
Wire Shelving		Quick Ship- Super Erecta Shelf wire 60"W x 21"D Metroseal, Greene epoxy coat corrosion resistant finish with Microban antimicrobial protection plastic split sleeves are included in each carton, NSF	12		
Post		74 1/2"H adjustable leveling bolt, post are grooved at 1" increments and numbered at 2" increments double grooved every 8", metroseal 3 green epoxy coated corrosion resistant finish with Microban antimicrobial protection	20		
Shelving unit wire		shelf wire 42 x 21 epoxy	8		
Work Table with Prep Sinks		Prep table Sink Unit, 2- compartment 96" W x 30" D x 45 3/4"H over all, (2) sinks located at right end, (1) 16"W x 20"D front to back x 8" deep sink bowl, (1) 16" W x 20" D front to back x 4" deep sink bowl, 10" H backsplash, includes 10" swing spout with 4" centers & Poly sliding cutting board, (1) stainless steel	2		

ITEM	BRAND	DESCRIPTION	QUANTITY	PRICE EACH	Company
		drawer on left, 16/300 stainless steel top, stainless steel legs, adjustable undershelf, and 1" adjustable bullet feet, NSF, CSA- Sanitation 2 standard flyer accessories only, no modifications to flyer items allowed or their accessories.			
work table		96" W x 30" D, 16/300 stainless steel top with 5" backsplash, with Stallion Safety Edge front, 90 degree turndown on sides, stainless steel legs and adjustable undershelf, adjustable bullet feet, NSF, CSA-Sanitation, KD (1) stander flyer accessory only, no modifications to flyer items or their accessories (1) Drawer for 30"D work tables 15"W x 20" front to back x 5" deep, stainless steel front and drawer pan, roller bearing slides, NSF, for stainless table tops only	1		
Custom Hood Package		Exhaust only wall canopy hood section 1 exhaust MUA (CFM) 1,650 1,403 Section 2 exhaust MUA (CFM) 1,650 1,238 Hood Dimensions, Supply Plenum front, collars, exhaust MUA 90"L x 54"W x 24"H 102"L x 18"W x 4"H (1) 9"W x 16"L (2) 16"W x 30"L Hood Supply Plenum Front , Collar, Exhaust MUA: 90:L x 54"W x 24"H 90"L x 18"W x 4"H (1) 9"W x 16"L (2) 16"W x 30"L	1		

ITEM	BRAND	DESCRIPTION	QUANTITY	PRICE EACH	Company
		Performance enhancing lip (P.E.L.) for up to 31% lower exhaust rates, sloped grease trough with enclosed grease cups per NFPA 96 requirements. Material -430 SS where exposed UL 170 listed without exhaust fire damper, filter baffle stainless steel, lights globe light fixtures, Factory mounted exhaust collar (s), factory mounted supply collar (s), continuous capture for multisection hoods exhaust air balancing baffle, factory mounted 3" back airspace, utility/fire cabinet mounted on the left air curtain supply (ASP) front with dampers stainless steal backsplash 120" (2) 18 in high ceiling enclosures on left front right			
		1 exhaust fan drive direct fan, motor 2hp, ODP, 208/60/3, 1725 rpm factory mounted, motor VFD rated without shaft grounding protection UL/cUL 705 listed- supplement SC Power ventilators for restaurant exh. Appliances Switch, NEMA-3R, toggle junction box mounted and wired hinge factory installed grease trap, aluminum wheel material unit warranty HERTZ 3,300 60 Cycle	1		
		1 GPFV-26-G24 roof curb tag quantity width length height KEF-1 roof curb 1 26 26 24, vented galvanized nominal curb size	1		
		1 tempered supply fan energy in/out 181.7/167.1 MBH 208/60/3 outdoor air only, aluminum mesh 16 x 20 x 2 (4) damper inlet, outdoor air intake position: end Discharge position: bottom, galvanized coating double wall installation, tempering on, VFD Control constant volume, access side: right hand, control center, heat inlet air	1		

ITEM	BRAND	DESCRIPTION	QUANTITY	PRICE EACH	Company
		sensor, ETL approvals, flame rod sensing, pilot ignition control. Unit rated gas pressure: 1/2 PSI Unit warranty			
		1 roof curb tag quantity width length height surface mounted sound curb, galvanized nominal curb size	1		
		1 Kitchen Control- constant volume qty 1 1 supply fan, utility cabinet on hood-left HD-1 left end on hood HD-1, UL/ULC Listed 300 SS enclosure, capture tank mounted temperature sensors with up to 5 times faster response full color touch screen control interface, exhaust max during fire, power for shunt trip, temperature interlock Automatically starts fans when cooking occurs in compliance with IMC temperature sensors installed (2), lights off during fire, hood light control, VFD for balancing 7ft touchscreen cable	1		
		1 Fire Suppression System	1		

ITEM	BRAND	DESCRIPTION	QUANTITY	PRICE EACH	Company
		Pre pipe with parts and factory coordinated installation hood fire suppression system, detection type mechanical, coverage appliance specific, hood mark (s) connected, mounting location utility cabinet on hood, system size 6 gallon, flow points maximum of 22			
		Options and Accessories for hood fire system provided from factory			
		OEM Regulated Release Assembly	1		
		3 gallon tank assembly	2		
		gas valve 2", mechanical	1		
		manual pull stations	1		
		hood microswitch	1		
		alarm initiating switch	1		
		metal blow off caps			
		1 gas valve mark, ansul, mechanical 2 in.	1		
		1 field hook up, hook up of detection line and supply line (included) surface mounting of the manual pull station charging and arming of the system permit included hood puff test fee included	1		
		Hood Installation	1		
Gas Oven		Combi Oven, Gas - oven/steamer (6) 18" x 26" full size sheet pan or (12) 12 " x 20" x 1" hotel pan capacity, 10" high resolution easy touch control panel, (4) cooking	1		

ITEM	BRAND	DESCRIPTION	QUANTITY	PRICE EACH	Company
		<p>modes: hot air, steam, combi- steam & retherm, LED light, triple pane right hinged door with anti-microbial hygienic door handle multi-point core temperature probe, pull out spray hose, ConvoClean + fully automatic hands free cleaning system, stainless steel construction, 0.5kW, 120v/60/1-ph, 7.5 amps 68,200 BTU, cJULus, NSF, Energy Star. Warranty C-Start cleaner kit</p>	1		
		<p>Pre installation site survey Natural Gas Door hinged right, standard RO system</p>			
		<p>Water treatment system cartridge</p>	1		
		<p>1 oven stand, open storage with shelf, stainless steel</p>	1		
Range		<p>36" Range , 6 Open Burners Natural Gas Endurance resistant range 36" (6) 30,000 BTU burners, lift off burner heads, standard oven , stainless steel front, sides, back riser and lift-off high shelf, fully MIG welded chassis, 6" adjustable legs, 215,000 BTU, CSA, NSF warranty</p>	1		
Refrigerated Base		<p>Refrigerated Base equipment stand One section, 36W x 33-1/2"D x 21-3/8" H, 4.6 cu ft.</p>	1		

ITEM	BRAND	DESCRIPTION	QUANTITY	PRICE EACH	Company
		(2) stainless steel drawers, accommodates pans up to 6" deep, capacity: (1) full size pan and (3) 1/6 size pans per drawer, digital temperature display, stainless steel top, full marine drip guard edge, front air intake, self-cleaning			
Griddle		Griddle Gas, Countertop Heavy duty Griddle, countertop, gas 36"W x 24" D cooking surface, 1" thick polished steel griddle plate, embedded mechanical snap action thermostat every 12", millivolt pilot safety, manual ignition, low profile, stainless steel front, sides, front grease trough, 4" back and tapered side splashes, 4" adjustable legs, 81,000 BTU, CSA Flame, NSF natural gas warranty	1		
Fryer		Gas Fryer, Battery floor model, (2) 50lbs. capacity each, built in filtration, thermo tube type design, temperature probe, millivolt control system, to include filter starter kit, drain safety switch, 4 GPM pump, stainless steel fry pots, doors and cabinets, (2) 12,000 BRU, casuals, NSF Millivolt Controller Standard 120v/60/1-pj, 8.0 amps, filter Right side, 1" rear gas manifold without shut off valve, fryer with filter natural gas warranty	1		
Work Table		work table, 60" stainless steel 60W x 30"D, 16/300 stainless steel flat top, with Stallion Safety Edge front and back 90 degree turndown on sides, stainless steel legs and adjustable undershelf, adjustable bullet feet, NSF, CSA-Sanitation standard flyer accessories only no modifications to flyer items allowed drawer, for 30"D worktables, 20W x 20", front to back x 5" deep, stainless steel front & drawer pan, self-closing, roller bearing slides. NSF, for stainless still table tops only	2		
Work Table		96" Stainless Steel Top	1		

ITEM	BRAND	DESCRIPTION	QUANTITY	PRICE EACH	Company
		96W x 30"D, 16/300 stainless steel flat top, with Stallion Safety Edge front and back, 90 degree turndown on sides, stainless steel legs and adjustable undershelf, adjustable bullet feet, NSF, CSA-Sanitation, KD standard flyer accessories only no modifications to flyer items allowed drawer, for 30"D worktables, 20W x 20", front to back x 5" deep, stainless steel front & drawer pan, self-closing, roller bearing slides. NSF, for stainless steel table tops only	1		
Pot Rack		Pot Rack, table mount, boat shaped, 91-1/4" W x 18-1/8"D x 48"H overall size, 3/16" x 2" stainless steel flat bar, includes (24) stainless steel double hooks, 16/300 stainless steel construction. NSF, CSA- Sanitation (requires factory installed bracket to JBC table	1		
Prep Refrigerator		Mega Top Sandwich/ Salad preparation refrigerator two section, 60"W, 20.20 cubic feet, (2) doors, (2) 1/1 GN shelves, stainless steel top with polyethylene cutting board (24) 1/6 size plastic pans, ABS interior sides, stainless steel front and sides, 5" casters, front breathing rear mounted refrigeration system , R290 Hydorcaron refrigerant, 0.35hp cUL, UL, NSF warranty, labor and parts compressor warranty 115v/60/1-ph, NEMA 5-16P, standard self-contained refrigeration, standard door (s), standard	1		
Drying Rack		Mobile Drying Rack unit, 48"W x 24"D x 68"H, 4 tier to include (4) shelves, (4) 63" mobile posts, (2) cutting board/ tray drying racks, (2) pan racks, (4) polymer swivel casters (2 with brakes), built in Mircoban Antimicrobial product protection, NSF	2		
Compartment Sink		Three (3) compartment sink, 111"w x 35-1/2"D x 44"H overall size, (3) 30"W x 30" front to back x 14" deep compartments (2) 24" left and right drainboards, 10"H boxed backsplash with	1		

ITEM	BRAND	DESCRIPTION	QUANTITY	PRICE EACH	Company
		45 degree top and 2" return, (1) set of splash mount faucet holes with 8" centers, 3-1/2" die- stamped drain openings, 16/300 stainless steel construction, stainless steel legs, adjustable side bracing, adjustable bullet feet, NSF, CSA-Sanitation standard flyer accessories only no modifications to flyer items allowed	1		
		Prerinse unit, splash mount, flex stainless steel hose, 8" centers, 1/4 turn ceramic cartridges, color coded hot/cold indicators integral check valve, 1/2" NPT, includes 12" wall bracket, NSF cCSAus, ADA compliant	2		
		twist handle lever waste, for 3-1/2" industry standard sink opening, standard valve, basket strainer (includes adapter for either 2" or 1-1/2" drain outlet)	3		
		pot rack wall mount, single bar 96"W x 12"D x 2"H overall size 3/16" x 2" stainless steel flat bar, includes (8) stainless steel double hooks, NSF, CSA-Sanitation	1		
Faucet		Wall/Splash mount faucet Sink Mixing Faucet, wall mount, 12" swing nozzle, 8" centers, 1/2" NPT male inlets, lever handles, quarter turn Eterna cartridges, low lead, ADA compliant	2		
Soiled Dish table		Pro-Bowl Soiled Dish table, straight design, 72"W x 30"D x 44"H overall size, left to right operation, (1) 20"W x 20" front to back x 8" deep pre-rinse sink bowl, 10"H boxed backsplash with 45 degree top and 2" return, (1) set of splash mount faucet holes with 8" centers 2-1/4"H rolled edge, 14/300 stainless steel top, stainless steel legs bracing, adjustable bullet feet, NSF specify dish machine brand and model (for modifications)	1		
Faucet Assembly		Pre-Rinse Faucet Assembly Easy Install, spring action gooseneck and hole base faucet, low flow 0.65 GPM spray valve (B-0107-C), 44" flexible stainless steel hose, 24" riser, 18" flexible supply lines, 6" wall bracket, quarter-turn Eterna cartridges, low lead, 2019 DOE PRSV-Class II	1		
Dishwasher		door type ventless dishwashing machine, energy recovery, high	1		

ITEM	BRAND	DESCRIPTION	QUANTITY	PRICE EACH	Company
		temp sanitizing, 208-240/60/3 (field convertible to single phase), internal condensing system, 45 racks/hour, straight- thru or corner installation, user friendly smart touchscreen controls, Wi-Fi capability, DeLime notification with cycle, Sense-A-Temp booster, electric tank hear, x-shaped wash arms, scrap screen and basket, door actuated start, door lock, stainless steel tank, tank shelf, chamber, trim panels, frame and feet, cULus, NSF, Energy Star warranty shipping			
Clean Dish table		pro-bowl clean dish table, straight design, 60"W x 30"D x 44"H overall size, left to right operation, 10"H boxed backsplash with 45 degree and 2" return, 2-1/4"H rolled edge, 16/300 stainless steel top, stainless steel legs, bracing and adjustable bullet feet, NSF specify dish machine brand and model (for modifications)	1		
Pizza Bake Oven		Electric, countertop, two compartment, (2) 18-1/8"W x 17-1/8" D x 3-5/8"H cooking chambers, (2) 16" pizza capacity, 86 degree - 608 degree temperature range, (2) double pane glass doors, variable speed impingement airflow, independently controlled top and bottom heaters, infrared heat, vent less with removable catalytic converter, manual mode to include (1) aluminum mesh screen, (1) aluminum paddle, AISI304 stainless steel interior, AISI304 stainless steel exterior, cETLus warranty parts and labor 208v/60/1-ph, 5.6 kw, 30 amps, cord, NEMA-6-30P, standard	1		
Worktable		work table 36"W x 36"D, 16/300 stainless steel top with 5" backsplash with Stallion Safety Edge front, 90 degree turndown on sides, stainless steel legs and adjustable undershelf, adjustable bullet feet, NSF, CSA-Sanitation, KD	1		
Refrigerator		Reach-In Refrigerator, one section, 23.4 cu. Ft. self- contained refrigeration, (1) full height solid door (hinged right) (2) epoxy coated shelves (factory installed), microprocessor control with LED display, LED interior lights,	2		

ITEM	BRAND	DESCRIPTION	QUANTITY	PRICE EACH	Company
		stainless steel front, anodized aluminum sides and interior, 6" high casters, R290 Hydrocarbon refrigerant, 1/4 HP, 115v/60/1, 3.8 amps, NEMA-5 15P, cETLus, ETL-Sanitation, Energy Star Casters 6", locking (set of 2) standard parts and labor warranty compressor warranty	2		
Heated Proofing Cabinet		Mobile Heated holding and Proofing cabinet with Grey Insulation Armor, full height, insulated, Dutch clear polycarbonate doors, removable bottom mount control module, thermostat to 200 Degree F. universal wire slides on 3" centers adjustable on 1 1/2" increments (18) 18" x 26" or (34) 12" x 20" x 2 1/2 pan capacity, 5" casters (2 with brakes), aluminum, 120v/60/1 ph., 2000 watts, 16.7 amps, NEMA 5 20P, cULus, NSF warranty	1		
Serving Counter		hot and cold, 14'L x 40"d x 34"H, die wall construction, standard laminate facades, FRP employee side, standard solid surface top, tray slide, stainless support legs. (3) equipment flanges, sneeze guard package	1		
Hot Food Well		Drop-in hot food well unit, electric, individual pans, wet/dry type with drain and manifold, 3-pan size for 12" x 20" pans, individual infante temperature controls, stainless steel top and wells, galvanized outer liner, (44-5/8" x 25" cutout required), cUL, UL, NSF 208-230v/60/1-ph, 15.0-16.0 amps, standard	1		
Light Fixture		Glo-Rite, Curved display light, strip type with aluminum housing and rocker switch, LED lights, 42" long, 10.8 watts, cULus, UL EPH Classified. warranty parts and labor 120v/60/1-ph, standard HL5-3050 warm white LED lights (3050k), standard HL5-LEAD10 10' extended electrical leads, includes 3' conduit standard clear anodized aluminum housing	2 2 2 2		
Heated Shelf Food Warmer		Glo-Ray Built in Heated Shelf with Flush Top, 49-1/2" x 25-1/2" surface area, hard coat aluminum top, control thermostat, illuminated	1		

ITEM	BRAND	DESCRIPTION	QUANTITY	PRICE EACH	Company
		on/off switch and mounting bracket, 1225 watts, NSF, CE, cUL, UL UL EPH Classified, CSA warranty parts and labor Thermostat control with lighted rocker switch countertop material suitable for temps up to 200 degrees F	1		
Heat Lamp		Glo-Ray Infrared Strip Heater, curved, 42"W, standard watt, dual LED lights, remote box with electronic infinite control, power on/off switch, mounting brackets, 686 watts 120v/60/1-ph clear anodized aluminum housing, finish standard LED-LEADS10 LED Wire, 10' total power lead length specify total lead length required GR5AL-WW warm white LED, standard warranty parts and labor	1 1 1 1 1		
Cold Food Well Unit		Drop-in, mechanically cooled pan, 43-1/2"W x 26"D, 3 pan size, 1" dia. drain, insulated pan, stainless steel inner liner and top, galvanized steel outer liner, includes adapter bars, self-contained refrigeration, R290 Hydrocarbon refrigerant, 2/7 hp, (42-1/2" x 25" cutout required), cUL, UL, NSF 115v/60/1-ph, 3.1 amps, NEMA 5-15P, Standard warranty parts and labor	1 1		
Open Display Merchandiser		Veumax Series Open Air-Merchandiser, 35-1/8"W x 31-3/4 "D x 83-1/8" H, 12.15 cu.ft capacity, tempered thermal glass sides, (5) shelves, price tag molding, night curtain, 36 degree F-40 degree operating temperatures, LED interior lighting, maintenance-free condenser, automatic defrost, R290 Hydrocaron refrigerant, painted steel interior, gray powder coated exterior, (2) 1/4 HP, cETLus, ETL- Sanitation 115v/60/1-ph, 12 amps, NEMA 5-20P Security cover, with lock warranty parts and labor	1 1 1		
Cash Register Stand		Cashier Counter 48"L x 40"D x 34"H Storage base, standard laminate exterior, tray slide standard solid surface	1		

ITEM	BRAND	DESCRIPTION	QUANTITY	PRICE EACH	Company
Beverage Station		8'L x 36"D x 34"H, storage base, standard laminate exterior, standard solid surface, steel top support, raised 4" backsplash FRP Interior	1		
Ice Maker		cube style, air-cooled, self contained condenser, dual exhaust top/slide air discharge, 30"W, approximately 561 lb. production/24 hours at 70/50 degrees (432 lb. at 90/70 degrees) half size cubes, PURE ICE built in antimicrobial protection, LED status display, one touch sanitize descaling controls, dishwasher safe food zone components, cULus, NSF CE, BPA Free 115v/60/1-ph, 17.8 amps, standard 510lb storage capacity ice bin, 30"W x 31"D x 50"H, top hinged, slope front door, for top-mounted ice maker, polyethylene interior, durable aluminum exterior, 69" legs, NFS warranty parts and labor warranty parts and labor compressor warranty parts and labor evaporator	1 1		
Drop in Sink		2 compartment, 33"W x 22"D x 12"H overall size, (2) 14"W x 16" front to back x 10" deep bowls, deck mount faucet holes with 4" centers, 3-1/2" drain opening with basket drain, stainless steel construction, NSF standard flyer accessories only no modifications to flyer items allowed Heavy duty Faucet, deck mount 10" swing spout, 4" centers, 1/4 turn ceramic cartridges, cooler coded hot/cold indicators, integral check valve, 1/2" NPT, chrome finish, NSF, cCSAus, ADA compliant (LEAD FREE FAUCET)	1 1		
Microwave Oven		Pro commercial microwave oven, 1000 watts, .08/ cu ft capacity, (6) power levels, 2 and 3 stage cooking, touch control pad, 99- minute timer, programmable and manual operation, program list/counter self diagnostics, tone control, bottom energy feed, interior light see through door with "grab and go" handle, stainless steel front, 12v/60/1-ph, 13.4 amps, cord, NEMA 5-15P, cULus, NSF warranty parts and labor	2		
Installation					

ITEM	BRAND	DESCRIPTION	QUANTITY	PRICE EACH	Company
Freight					
Time to Complete					